HKJC Amphitheatre - Venue Information 香港賽馬會演藝劇院 - 場地資料

Auditorium 觀眾席 Sound 音響 Others 其它 Stage 舞台 Lighting 燈光 Projection 投影 Continental Seating-Thrust Stage-Control-Control-Control-Dressing Roomswith three sides audiences 三向舞台 -控制室· 控制室 -控制室 化粧間 With access codes door locks Raked Floor-Flat floor stage Room located in auditorium - rear center Room located in auditorium - rear center Room located in auditorium - rear center 沿斜地面 -Floor Surface-Console House Console-Projection Screen-配備密碼門鎖 台面結構 -調控台 主調音台 -投影幕 -U shape seating platform Accommodating 14 persons with **Seating Capacity** 600 nos. Beech timber dance floor ETC EOS GIO (DMX 2048) Lighting Console Yamaha QL5 Digital Mixing Console Oray Matt White electric roller screen Dressing room A for 7 persons at SR 座位總數 -**Dimmer Control-**- Local In & Out: 32 in & 16out (25m²/269ft²) Floor loading (500kg/m²) Size: 11m(W) x 7.5m(H) 600 seats from row A to H Performing Area-調光器 -- Input channels to mix: 64 mono and 8 Stereo Dressing room B for 7 persons at SL Maximum image size: include 4 wheelchair seats in row A 演出面積 -ETC Sensor HSR dimmers system - Busses: 16 mix and 8 matrix for 4:3 format: 10m(W) x 7.5m(H) (22m²/237ft²) Wheelchair entrance is at the U shape stage about 16m(W) x 17m(D) 60 x 2.5 KW dimmers - Fader: 32+2 for 16:9 format: 10.8m(W) x 6m(H) Artists' Facilities-Control Patch-Signal Processing Equipment-Projector lift and locationbackstage entrance on ground floor Permanent Installation-表演者設施 -(輪椅使用者請從後台出入口進場) 固定裝置 -接駁控制 -訊號處理器材 -投影機位置 -Show relay / cast call paging Tunable acoustics via reversible reflective / Mains patch individually BSS FCS960 equalizer At rear centre of auditorium ceiling En suite shower & toilet absorptive panels at rear of auditorium Luminaires-BSS DPR series comp/ limiter Throw distance: 23.5m in dressing rooms Suspension System-燈類 -Lexicon PCM70 reverb unit SVS 7 Series lift platform for projector: CCTV monitor viewing stage 懸掛系統 -Standard Rig re plan XTA GQ600 equalizer Max. size: 0.75m(W) x 1.2m(D) x 0.6m(H) One 16m motor bar in front of timber back wall Yamaha SPX990 multi-effect processor (Max. SWL 100kg) Seachanger Wash w/ ETC S4 Lamp Housing x 16 for OH top height 8.2m above stage floor Playback Equipment-Power outlet: Ceenorm 32A single phase (Total SWL 500kg) ETC Source Four 750W 26° x 12 for OH Video Playback Equipment-錄像重播器材 -Four fixed lighting bars installed along ETC Source Four 750W 26° x 20 for FOH Tascam CD-01U PRO professional CD player Tascam SS-CDR200 Multi-media player/ Recorder slope ceiling truss ETC Selador Vivid 42"R x 8 for CYC Lights Support SD and HD video formats (Total SWL 500kg each) VARI-LITE VL1100 TSD x 14 mainly for OH Microphone-Two fixed lighting bars installed along 麥克風 Follow Spottwo wings above rear of auditorium 追光 -**DYNAMIC** -(Total SWL 1000kg each) Robert Juliat Manon 1.2kW HMI x 2 動圈式 -Get In-Lighting Position-AKG: D12VR, D541E, D90S 燈光位置 -AUDIX: D4, OM6 Loading dock entrance 1m(W) x 2.2m(H) Four fixed lighting bars installed along Flectro-Voice: RF-20 Sennheiser: BF 531, e 835-S, MD 421, at back of stage right slope ceiling truss Sliding timber wall panel to allow get in of (Max rigging height above stage floor: 11m) MD 422. MD 738FE long scenery items Two fixed lighting bar installed along Shure: Beta 57A, Beta 58, SM57, SM58 CONDENSER -Stage Equipmenttwo wings above rear of auditorium 舞台配備 -電容式 -(Rigging heights from 2.95m to 3.5m) Musician chair x 80 nos AKG: CK1, GN30, GN50 Auxiliary Power Supplies-Music stand x 80 nos. 輔助供電 AUDIX: M1250 "Genie" aerial work platform AWP-40S 220V 50Hz (Single Phase) DPA: dfacto II FA4018, SC4098-BX45, Max platform height: 12m Control Room 63Amps - 3 phase 4099, 2011C Connection - Terminals Neumann: KM140, KM184 (Only for trained person and must have venue Require: WR1 issued by REW & REC Ramsa: WM-S5E (須要場地管理之允許及有操作經驗者方可使用) (需要電業工程人員及承辦商簽發WR1) Sennheiser: BF 5032 The Academy reserves the right to amend or update venue facilities without notice. REW (Registered Electrical Worker) Shure: SM85, SM87 演藝學院保留更改及更新場地設施的權利, 恕不另行通知. REC (Registered Electrical Contractor) Wireless Microphone -無線麥克風 -Optional equipment for which an additional daily hire charge will apply. # # 選擇性器材及需要額外日租計算.# Sennheiser Evolution 500 series with (Lavalier or Handheld Microphone) ** These items are shared amongst several venues - their availability for a particular hiring is at the management's sole discretion. ** 此等項目分配於各場地使用-場地管理就個別租用者要求而提供可使用的數量.

HKJC Amphitheatre - Venue Information 香港賽馬會演藝劇院 - 場地資料

Auditorium 觀眾席 Stage 舞台 Lighting 燈光 Sound 音響 Projection 投影 Others 其它

Fixed House PA System-

固定揚聲系統 -

- One d&b Qi7 loudspeaker plus one d&b Qi-SUB sub woofer per side for main stereo system
- Three d&b Qi7 loudspeaker for overhead cluster speakers
- Yamaha DME24N digital mixing engines with fixed EQs and system delay data

** Mobile Speakers-

流動揚聲器 -

- Fender: SPL-1282
- Sound Project: X-act self-powered monitor

Communication-

劇院通訊系統 -

- Intercom system available at all control points
- Telex wireless intercom system
- Cast call paging system to dressing rooms
- Infrared monitor viewing stage
- CCTV monitor viewing stage at control room, backstage, dressing rooms
- CCTV monitor in audiences lobby for latecomer

The Academy reserves the right to amend or update venue facilities without notice. 演藝學院保留更改及更新場地設施的權利, 恕不另行通知.

- # Optional equipment for which an additional daily hire charge will apply.#
- # 選擇性器材及需要額外日租計算.#
- ** These items are shared amongst several venues their availability for a particular hiring is at the management's sole discretion.
- ** 此等項目分配於各場地使用-場地管理就個別租用者要求而提供可使用的數量.