<u>Lyric Theatre - Venue Information 歌劇院 - 場地資料</u>

Auditorium 觀眾席	Stage 舞台	Lighting 燈光	Sound 音響	Projection 投影	Others 其它
Continental Seating in Circle and	Proscenium Stage-	Control-	Control-	** Projection Screens-	** Dressing Rooms-
Gallery, Stalls seats divided by-		控制室 -	控制室 -	投影幕 -	化粧間 -
two aisles-	- Flat floor with 2 forestages lifts for	- Room located in auditorium - circle rear left	- Room located in auditorium - stalls rear center	# EZ Folo portable (Front or Rear) 25'(W) x 18'(H) #	** Subject to availability
Raked Floor-	small / large pit / thrust stage	Console-	House Console-		供求視乎實際情況
沿斜地面 -	Floor Surface-	調控台 -	主調音台 -		- Equip with access codes locks
Full Seating 1,181 nos.	台面結構 -	- ETC EOS Titanium(Eos Ti™) (DMX_4096) with	- DiGiCo Quantum 338 Digital Mixing Console		配備密碼門鎖
座位總數 -	- Hardboard over sprung T & G floorboards	moving light control / effects /	128 Input channels, 58 Aux / Sub-Group Busses		- Accommodating 89 persons tota
- Stalls 466 nos.	- Stage floor loading (500kg/m²)	netware options and full backup system	18 x 18 Matrix out		- No.1-5 stage level stage right
- Circle 274 nos.	Dance Flooring-	- Strand STM 390 dimmers	- 2nd Console DiGiCo Quantum 388		- No.7-14 below stage level with
- Gallery 441 nos.	跳舞地膠 -	- ETC Sensor3 ThruPower dimmers x 40	last two row of auditorium stalls level		staircase access to both sides
- Pit 2 used 1,143 nos.	- Grey / Black mat	8 x 10kW, 92 x 5kW, 330 x 2kW	- Control room SD-Rack Layout:		- DR1 for 3 persons(19m ² /205ft ²)
- Pit 1 + Pit 2 used 1,093 nos.	Proscenium Opening-	Control Patch-	48 analog inputs, 32 analog outputs, 4 In & 4Out AES		- DR2 for 2 persons(17m ² /180ft ²)
- 4 wheel-chair spaces at circle	台口面積 -	- 接駁控制 -	Two floating SD-Rack at Stage/Pit:		- DR3 for 5 persons(26m²/278ft²)
·	- Variable 12.8 - 18m(W) x 6 - 9m(H)	- At switchboard	32 analog inputs, 16 analog outputs		- DR4 for 2 persons(17m²/180ft²)
	- Stage floor 0.9m above auditorium floor	- Mains patch individually	- One floating Mini-Rack:		- DR5 for 2 persons(14m ² /150ft ²)
	Forestage-	Lektriflex multicore at Gallery	16 analog inputs, 8 analog outputs, 4 In & 4Out AES		 DR7 for 4 persons(24m²/260ft²)
	幕前副台 -	Luminaires-	- Signal Processing Equipment-		 DR8 for 6 persons(25m²/270ft²)
	- Depth of apron in front of the	燈類 -	- 訊號處理器材 -		 DR9 for 4 persons(20m²/220ft²)
	setting line 2.08m or 4.48m	- FOH-	- BSS FCS960 equalizers		- DR10 for 13 persons(51m²/553f
	Orchestra Pit-	- ETC Source Four 750W 10° x 22	- BSS DPR series comp/ limiters		- DR11 to 14 for 12 persons each
	樂池 -	- ETC Source Four 750W 14° x 14	- Lexicon PCM70 reverb unit		(around 50m²/538ft² each)
	- 15.6m(W) x 3.5m(H) x 6.1/3.5m(D)	- ETC Source Four 750W 19° x 30	** XTA GQ600 equalizers		Artists' Facilities-
	accommodating 60 / 30 persons	- ETC Source Four Zoom 15° - 30° x 10	Yamaha SPX990 multi-effect processor		- 表演者設施 -
	88 / 38 seats lost through use	- ETC Source Four EDLT 750W 19° x 10	- Playback Equipment-		- Show relay / cast paging
	Performing Area-	- ETC Source Four EDLT 750W 26° x 10	- 重播設備 -		- Showers in each room
	演出面積-	- Robert Juliat 710SX (10/25) 2kW x 10	** Marantz PMD331/ 340 CD player		- CCTV by arrangement
	- Main stage (主台)	Robert Juliat 714SX (15/40) 2kW x 10	Tascam SS-CDR200 Multi-media player/ Recorder		Telephone at Company Office &
	24m(W) x 16m(D) x 27m(H) to Grid	- STAGE-	Microphone-		stage Right corridor
	- Rear stage (後台)	- ETC Source Four 750W 26° x 20	····································		- Laundry / Wardrobe facilities
	18m(W) x 13m(D) x 8.8m(H) to Ceiling	- ETC Source Four Zoom 15° - 30° x 20	- DYNAMIC-		- Quick change temporary setup
	- Side stage (側台)	- ETC Source Four Zoom 25° - 50° x 20	- 動圏式 -		- Quick change temporary setup
	12.8m(W) x 14m(D) x 8.8m(H) to Ceiling	- CCT Starlette Fresnel 1kW x 30	- AKG: D12VR. D541E. D90S		
	Flying System-	- CCT Starlette Fresnel 2kW x 60	- AUDIX: D4, OM6		
	R杆系統 -	- Parcan 64 1kW x 50	Electro-Voice: RE-20		
	- 63 single purchase counterweight bars	- Quartz Orion 1kW G.Row x 12	- Sennheiser: BF 531, e 835-S, MD 421,		
	4 double purchase side counterweight bars	Strand IRIS 4 1kW Cyc. Flood x 8	MD 422, MD 738FE		
	(safety loading 600kg per bar)	Follow Spot-	Shure: Beta 57A, Beta 58, SM57, SM58		
	- 10 motorized bars	- 追光 -	- CONDENSER-		
		- 短元 - ** Robert Juliat Cyrano 2.5kW HMI x 3	- 電容式 -		
	6 motorized bars (stage left and stage right)	Extra Luminaires-	- 电合式 - - AKG: CK1, GN30, GN50		
	3 motorized bars in front of the proscenium arch	-Share with other venues	- AKG: CK1, GN30, GN30 - AUDIX: M1250	The Academy reserves the right to amend or update ve	nue facilities without notice
	(safety loading 750kg per bar)	額外燈類 - 與其他場地共用		演藝學院保留更改及更新場地設施的權利, 恕不另行通知.	nue racinties without notice.
	- Rear stage 5 electric winch bars	額外短類-與兵心場地共用 -PROFILES-	Crown: PCC160 - DPA: dfacto II FA4018, SC4098-BX45,	展察学院派由文以及史制物也改能的推判,必个为门地址。 # Optional equipment for which an additional daily hire c	harge will apply #
	(safety loading 250kg per bar)			# 返擇性器材及需要額外日租計算#	пагус иш арргу.п
	- Side stage 3 hand winch bars	- ETC Source Four 750W 26° x 20	- 4099, 2011C	# 選岸性語句及需要調外口性計算。# ** These items are shared amongst several venues - their availability for a particular	
	(safety loading 250kg per bar)	- ETC Source Four Zoom 15° - 30° x 30	- Neumann: KM140, KM184	_	avanability for a particular
	- Fixed bars at auditorium circle and gallery front	ETC Source Four Zoom 25° - 50° x 20	- Ramsa: WM-S5E	hiring is at the management's sole discretion.	3.供司体用的数量
	(safety loading 150kg per bar)	- FRESNELS-	** Sennheiser: BF 5032	** 此等項目分配於各場地使用-場地管理就個別租用者要求而提	医内引成用的数里。
		- CCT Minuette 650W x 10	Shure: SM85, SM87	I	
		- CCT Starlette 2kW x 6			Venue Techni

ADB TVM 5000 5kW x 4

Venue Technical Nov, 2024

Venue Technical

Nov, 2024

Lyric Theatre - Venue Information 歌劇院 - 場地資料

Auditorium 觀眾席 Others 其它 Stage 舞台 Lighting 燈光 Sound 音響 Projection 投影 Permanent Attachment-Wireless Microphone-固定裝置 ARRI HMI 2.5kW Fresnel x 1 # 無線麥克風 ARRI HMI 4kW Fresnel x 1 # House Curtain (line CW7) Sennheiser Digital 6000 series Acoustic Shell ceiling panels on line FM5, M2 PARCAN-Sennheiser Evolution 500 series M6, CW16, CW25, CW34, CW43 and CW52 Parcan 64 1kW x 16 (Both series, with Lavalier or Handheld microphone) Flying Bar Lengths (Main) -Altman Zip Strip 50W 12 Degree Fixed House PA System-吊杆長度 -MR16 Borderlight 2'-2" x 4, 6'-4" x 9 固定主揚聲系統 -18m. extendable to 22m * Thomas Cvc. Flood 4 1kW x 5 Seven d&b audiotechnik Qi1 line array loudspeakers Masking & Soft Hanging-Scenic Projectionplus two Qi-SUB sub-woofers per side for 投影效果 -Main Fill Left & Right 增导帳菓及掛菓-Pani BP-2 2kW x 4 Green velour house curtain Eight d&b audiotechnik T10 line array loudspeakers Pani Effect Motor Unit for Pani BP-2 x 4 2 sets black full tabs, size: 20m(W) x 10m(H) for Main Centre Array Flame wheel x 2 2 sets black half tabs, size: 12m(W) x 10m(H) Five d&b audiotechnik 4S full range speakers 6 black borders, size: 20m(W) x 5m(H) Fleecy cloud wheel x 2 for Front Fill at Front of Stage - 5 pairs of black legs, size: 5m(W) x 10m(H) Stormy cloud wheel x 2 Two d&b audiotechnik 10S full range speakers Flat cyclorama screen for front and Water wheel x 2 for Upper Gallery Fill hang on Light Bridge 2 back projection, size: 18m(W) x 10m(H) **Lighting Position-**Two d&b audiotechnik 8S full range speakers Black gauze & White gauze, 20m(W) x 10m(H) 燈光位置 for Gallery Side Box Fill hang on Light Bridge 1 Various black masking flats FOH-* Six Apogee AFI-2 two-way full range speakers for SL Side masking on track - L/R Perches x 2 surround system (Rear) installed at rear of stalls, SR Side masking on line M63, M64 # L/R Slot x 6 circle and upper gallery Light Bridge x 3 BSS Soundweb programmable signal processing Get in-入景 -Circle front and Gallery front system with fixed EQs and system delay data Through Loading Bay STAGE-Mobile Speakers-Minimum dimensions (4.4m(H) max) sufficient to Wired spotbar x 7 流動揚聲器 · accommodate 40' container(High Cube) Mobile ladder x 8 Apogee: ACS-2 Loading platform 0.95m above driveway level Mobile side light tower x 8 Bose: 402, 32se Goods lift access to all floors Smoke Machines-Duran Audio: U-14 self-powered loudspeaker Stage Equipment-煙機 -Fender: SPL-1282, SPL-1285 舞台配備 · Le Maitre MVS Hazer x 2 Galaxy Audio: GHSVC monitor. Cougar XLT 2900 hydraulic lift max, 8.8m(H) - Le Maitre MVS Smart Hazer x 2 GPA5XD140 self-powered monitor ** Smoke Factory Captain D x 4 Instant Tallescope 50518: 3.5m - 5.9m(H) LEM self-powered loudspeaker: SPN6A, T3A, Instant Tallescope 50524: 4.6m - 7.5m(H) T5A, T5MA, T5SA Accessories-- Musician chair x 100 nos 其它配備 -Meyer Sound: UPM-1P self-powered loudspeaker Illuminated music stand x 60 nos. Peasouper dry ice machine x 1 Tannoy Wildcats series (Jaguar, Puma) Non-illuminated music stand x 90 nos. - Aquafog 3300 dry ice machine x 2 Communication-A range of Lee filters stocked 劇院通訊系統 -Piano-Stage Manager's desk at Stage Right with talkback UV lamp x 2 鋼琴 -Martin Atomic 3000 DMX Strobe light x 2 # Kawai Concert Grand Piano (GS100) # system, cue light system, cast call paging system **Auxiliary Power Supplies-**Yamaha Baby Grand Piano (C6) to dressing rooms, CCTV monitor viewing stage 輔助供電・ The Academy reserves the right to amend or update venue facilities without notice. Yamaha Upright Piano (U1A) and conductor 演藝學院保留更改及更新場地設施的權利, 恕不另行通知. Acoustic Setup 220V 50Hz (Single Phase) Intercom system available at Theatre all control points Optional equipment for which an additional daily hire charge will apply.# Orchestral Concert 18m(W) x 12m(D) Rear stage 300Amps - 3 phase Green-Go wireless intercom system # 選擇性器材及需要額外日租計算.# Chamber Concert 14m(W) x 7.5m(D) Side stage 300Amps - 3 phase Infrared monitor viewing stage ** These items are shared amongst several venues - their availability for a particular Connection - Bus Bars CCTV monitors in all foyers for latecomer hiring is at the management's sole discretion. Require: WR1 issued by REW & REC **Auxiliary Sound Power Supplies-*** 此等項目分配於各場地使用-場地管理就個別租用者要求而提供可使用的數量. (需要電業工程人員及承辦商簽發WR1) 音響專用輔助供電 REW (Registered Electrical Worker) 220V 50Hz (Single Phase)

Side stage 32Amps - Single Phase x 2

Connection - Socket

REC (Registered Electrical Contractor)